



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Wall _____

Surface _____

White Matt _____

RAL 9010 ^a _____

IP20 _____

Interior _____

total 820 lm _____

LED

colour warm dimming _____

1800 K - 2850 K _____

CRI ≥ 90 _____

initial MacAdam ≤ 3 SDCM _____

OPTICAL

Variable _____

ELECTRICAL

phase-cut dim _____

220 - 240 V _____

11.0 W _____

Class 1 _____


PHYSICAL

diameter 150 mm _____

height 100 mm _____

0.69 kg _____

^a Colour may deviate slightly due to production conditions.



[‘342148W9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.