




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Cylindrical wall surface mounted luminaire made from aluminium; surface Aluminium Brushed; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Wall _____
 Surface _____
 Aluminium Brushed _____
 IP20 _____
 Interior _____
 total 820 lm _____

LED

colour warm dimming _____
 1800 K - 2850 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Variable _____

ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 11.0 W _____
 Class 1 _____

PHYSICAL

diameter 150 mm _____
 height 100 mm _____
 0.69 kg _____

[‘342148L9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.