



**PROJECT**

---

**TYPE**

---

**NOTES**

---

**QUANTITY**

---

**DATE**

---



Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing White Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; degree of protection IP20; Class 1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500$  cd/m<sup>2</sup>; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**GENERAL**

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 White Matt + Gold \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 770 lm \_\_\_\_\_  
 CIE flux code: 99 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L70 / 55000h \_\_\_\_\_  
 initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

**OPTICAL**


Standard \_\_\_\_\_  
 beam angle 32° \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 11.0 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

length 94 mm \_\_\_\_\_  
 width 50 mm \_\_\_\_\_  
 height 80 mm \_\_\_\_\_  
 0.3 kg \_\_\_\_\_



[151264J5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



## Maintenance Factor

|                    |        |        |        |        |        |
|--------------------|--------|--------|--------|--------|--------|
| Operating Time [h] | 10.000 | 20.000 | 30.000 | 40.000 | 50.000 |
| LLMF               | 0.9    | 0.88   | 0.85   | 0.83   | 0.81   |
| LSF                | 1      | 1      | 1      | 1      | 1      |

MF  $LMF \times RSMF \times LLMF \times LSF$

MF Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor

RSMF<sup>a</sup> Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## MOUNTING ACCESSORIES

### 1.0 Ceiling Base

| Type         | Colour | L·W·H (MM) | Item number |
|--------------|--------|------------|-------------|
| PIRRO SYSTEM | White  | 754-51-12  | 90052072    |
| PIRRO SYSTEM | Black  | 754-51-12  | 90052073    |
| PIRRO SYSTEM | Gold   | 754-51-12  | 90052074    |

### 2.0 Ceiling Base

| Type         | Colour | L·W·H (MM) | Item number |
|--------------|--------|------------|-------------|
| PIRRO SYSTEM | White  | 1150-51-12 | 90052075    |
| PIRRO SYSTEM | Black  | 1150-51-12 | 90052076    |
| PIRRO SYSTEM | Gold   | 1150-51-12 | 90052077    |

## OPTICAL ACCESSORIES

### Honeycomb Louver

| Type                              | Colour | Ø (MM) | Item number |
|-----------------------------------|--------|--------|-------------|
| BLIEK PETIT   CENO   LECA   PIRRO | Black  | 29     | 90051131    |