



WEVER & DUCRÉ  
LIGHTING

# MAP ASYM 1.6

751658I4

Project
Type
Notes
Quantity
Date

## GENERAL

Floor  
 Recessed  
 Inox  
 IP67  
 IK09  
 Exterior  
 845 lm

## LED

3000 K  
 CRI  $\geq$  90  
 L60 / 50000 h  
 3-step binning

## OPTICAL

Wallwasher

## ELECTRICAL


phase-cut dim  
 220 - 240 V  
 Total connected power 15.7 W  
 Class 2  
 Safety distance 0.3 m

## PHYSICAL


Diameter 160 mm  
 Height 135 mm  
 1.7 kg

## CUTOUT


Diameter 150 mm  
 Recessed depth 185 mm



Round floor recessed luminaire made from stainless steel and glass; asymmetric light beam; surface Inox; recessed depth 185 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# MAP ASYM 1.6

751658I4

## MOUNTING

### Recessed Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 1.6   CHART 1.6	Ø213 · 175	9 0 0 1 2 2 0 4