

Project
Type
Notes
Quantity
Date

GENERAL

Floor
Recessed
Inox
IP67
IK08
Exterior
310 lm

LED

3000 K
CRI ≥ 90
3-step binning

OPTICAL

Beam angle 43°

ELECTRICAL


phase-cut dim
220 - 240 V
Total connected power 5.0 W
Class 2
Safety distance 0.3 m

PHYSICAL


Diameter 55 mm
Height 95 mm
0.4 kg

CUTOUT


Diameter 38-40 mm
Recessed depth 100 mm



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 100 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≈ 3 SDCM; CRI ≈ 90 ; beam angle 43°; degree of protection IP67; PC2; driver not included; light source replaceable by an authorized professional;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

MAP 0.6

751168I4

CONE DIAGRAM

0°

h (m)	E0° (lx)	ø (m)
1	0	0.00
2	0	0.00
3	0	0.00
4	0	0.00
5	0	0.00

MOUNTING

Recessed Housing

TYPE

MAP 0.6 | CHART 0.6

Ø · H (MM)

ø132 · 105

ORDERCODE

9 0 0 1 2 0 1