



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



**GENERAL**

Floor \_\_\_\_\_  
 Standing \_\_\_\_\_  
 tilt max 135 ° \_\_\_\_\_  
 Bronze \_\_\_\_\_  
 IP65 \_\_\_\_\_  
 Exterior \_\_\_\_\_  
 500 lm \_\_\_\_\_  
 CIE flux code: 93 99 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L70 / 55000h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_  
 beam angle 38° \_\_\_\_\_  
 UGR < 19 \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 6.7 W \_\_\_\_\_  
 Class 2 \_\_\_\_\_

**PHYSICAL**

diameter 52 mm \_\_\_\_\_  
 height 120 mm \_\_\_\_\_  
 0.52 kg \_\_\_\_\_



Cylindrical outdoor floor projector; surface Bronze; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; 135° tiltable; degree of protection IP65; Class 2; fixation base not included; driver included; optional ground spike available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[737468Q5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**BASE**

**Ground Spike**

| Type      | Ø-H (MM) | Item number |
|-----------|----------|-------------|
| STAKE 1.0 | 43-212   | 90013106    |

**Pole 200**

| Type                        | Colour          | Ø-H (MM) | Item number |
|-----------------------------|-----------------|----------|-------------|
| STIPO   with fixation plate | Anthracite Grey | 45-200   | 910062A0    |
| STIPO   with fixation plate | Bronze          | 45-200   | 910062Q0    |

**Pole 400**

| Type                        | Colour          | Ø-H (MM) | Item number |
|-----------------------------|-----------------|----------|-------------|
| STIPO   with fixation plate | Anthracite Grey | 45-400   | 910064A0    |
| STIPO   with fixation plate | Bronze          | 45-400   | 910064Q0    |

**Pole 600**

| Type                        | Colour          | Ø-H (MM) | Item number |
|-----------------------------|-----------------|----------|-------------|
| STIPO   with fixation plate | Anthracite Grey | 45-600   | 910066A0    |
| STIPO   with fixation plate | Bronze          | 45-600   | 910066Q0    |