



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Floor _____
 Standing _____
 tilt max 135 ° _____
 Anthracite Grey _____
 RAL 7016 ^a _____
 IP65 _____
 Exterior _____
 500 lm _____
 CIE flux code: 93 99 100 100 _____
 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 L70 / 55000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Standard _____
 beam angle 38° _____
 UGR < 19 _____

ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 6.7 W _____
 Class 2 _____

PHYSICAL

diameter 52 mm _____
 height 120 mm _____
 0.52 kg _____



Cylindrical outdoor floor projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; 135° tiltable; degree of protection IP65; Class 2; fixation base not included; driver included; optional ground spike available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

^a Colour may deviate slightly due to production conditions.



[737468A5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



BASE

Ground Spike

Type	Ø-H (MM)	Item number
STAKE 1.0	43-212	90013106

Pole 200

Type	Colour	Ø-H (MM)	Item number
STIPO with fixation plate	Anthracite Grey	45-200	910062A0
STIPO with fixation plate	Bronze	45-200	910062Q0

Pole 400

Type	Colour	Ø-H (MM)	Item number
STIPO with fixation plate	Anthracite Grey	45-400	910064A0
STIPO with fixation plate	Bronze	45-400	910064Q0

Pole 600

Type	Colour	Ø-H (MM)	Item number
STIPO with fixation plate	Anthracite Grey	45-600	910066A0
STIPO with fixation plate	Bronze	45-600	910066Q0

[737468A5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.