



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical outdoor floor projector; surface Bronze; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI \geq 90; 220 - 240 V; 135° tiltable; degree of protection IP65; Class 2; fixation base not included; driver included; optional ground spike available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Floor
 Standing
 tilt max 135 °
 Bronze
 IP65
 Exterior
 450 lm
 CIE flux code: 97 100 100 100
 100

LED

3000 K
 CRI \geq 90
 L70 / 55000h
 initial MacAdam \leq 3 SDCM

OPTICAL

Standard
 beam angle 38°
 UGR < 19

ELECTRICAL

phase-cut dim
 220 - 240 V
 6.7 W
 Class 2

PHYSICAL

diameter 52 mm
 height 164 mm
 0.53 kg



[737368Q5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



BASE

Ground Spike

Type	Ø-H (MM)	Item number
STAKE 1.0	43-212	90013106

Pole 200

Type	Colour	Ø-H (MM)	Item number
STIPO with fixation plate	Anthracite Grey	45-200	910062A0
STIPO with fixation plate	Bronze	45-200	910062Q0

Pole 400

Type	Colour	Ø-H (MM)	Item number
STIPO with fixation plate	Anthracite Grey	45-400	910064A0
STIPO with fixation plate	Bronze	45-400	910064Q0

Pole 600

Type	Colour	Ø-H (MM)	Item number
STIPO with fixation plate	Anthracite Grey	45-600	910066A0
STIPO with fixation plate	Bronze	45-600	910066Q0