



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Floor
 Standing
 tilt max 135 °
 Bronze
 IP65
 Exterior
 500 lm
 CIE flux code: 93 99 100 100
 100

LED

3000 K
 CRI ≥ 90
 L70 / 55000h
 initial MacAdam ≤ 3 SDCM

OPTICAL

Standard
 beam angle 38°
 UGR < 19

ELECTRICAL


phase-cut dim
 220 - 240 V
 6.7 W
 Class 2

PHYSICAL

diameter 52 mm
 height 120 mm
 0.56 kg



Cylindrical outdoor floor projector; surface Bronze; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; 135° tiltable; degree of protection IP65; Class 2; driver included; optional ground spike available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[737268Q5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

737268Q5



BASE

Ground Spike

Type

STAKE 1.0

Ø·H (MM)

43·212

Item number

90013106