



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



**GENERAL**

Wall  
 Surface  
 White Matt  
 RAL 9010 <sup>a</sup>  
 IP65  
 Exterior

**LED**

3000 K  
 CRI ≥ 90  
 initial MacAdam ≤ 3 SDCM

**OPTICAL**

Variable

**ELECTRICAL**

phase-cut dim  
 220 - 240 V  
 6.0 W  
 Class 1


**PHYSICAL**

diameter 150 mm  
 height 100 mm  
 0.47 kg



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

<sup>a</sup> Colour may deviate slightly due to production conditions.





**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.