



PROJECT

---

TYPE

---

NOTES


---

QUANTITY


---

DATE

---



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; optional single inner reflector and single inner cover available; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; 220 - 240 V; degree of protection IP65; PC1; light source replaceable by an authorized professional;



[735464B2] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



## OPTICAL ACCESSORIES

### Single Inner Cover

Type	Colour	Ø-H (MM)	Item number
RAY   max. 10W	Anthracite Grey	67-54	911041A1
RAY   max. 10W	Black	67-54	911041B1
RAY   max. 10W	Dark Grey Texture	67-54	911041D1
RAY   max. 10W	White	67-54	911041W1