



500384B5



#### **PROJECT**

**TYPE** 

**NOTES** 

QUANTITY

DATE












System luminaire for wall-/ceiling surface mounting or suspended mounting (2000 mm cable suspension available as accessory); surface Black Matt; powder coated; matt texture; RAL 9005; opal PMMA cover; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; 220 - 240 V; degree of protection IP20; Class 1; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



#### **GENERAL**

Ceiling / Wall
Surface
Black Matt
RAL 9005 <sup>a</sup>
IP20
Interior
1110 lm
CIE flux code: 48 80 96 100
100

## LED

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 3 SDCM

### OPTICAL

Opal

# **ELECTRICAL**

phase-cut dim	
220 - 240 V	
system 19.5 W	
Class 1	

## **PHYSICAL**

length 1314 mm	
width 30 mm	
height 80 mm	
1.7 kg	

<sup>&</sup>lt;sup>a</sup> Colour may deviate slightly due to production conditions.



### 500384B5



#### **Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>&</sup>lt;sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

### TRACK ACCESSORIES

#### **Connector Point**

Туре	Colour	Item number
ELLO	Black	900190B1
ELLO	White	900190W1

### Power Feeder for phase-cut dim

Type	Colour	Length (MM)	Item number
ELLO	White	2000	90018010
ELLO	Black	2000	90018011

## **Suspension Cable 2.0m**

Туре	Length (MM)	Item number
ELLO	2000	90015102