



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Wall
 Surface
 White Matt
 RAL 9010 ^a
 IP20
 Interior
 350 lm

LED

2700 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

OPTICAL

Variable


ELECTRICAL

phase-cut dim
 220 - 240 V
 system 6.0 W
 Class 1

PHYSICAL

diameter 150 mm
 height 100 mm
 0.62 kg

^a Colour may deviate slightly due to production conditions.



[‘342168W3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.