



PROJECT

---

TYPE

---

NOTES

---

QUANTITY


---

DATE

---



Cylindrical wall surface mounted luminaire made from aluminium; surface Aluminium Brushed; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**GENERAL**

Wall  
 Surface  
 Aluminium Brushed  
 IP20  
 Interior  
 330 lm

**LED**

colour warm dimming  
 1800 K - 2850 K  
 CRI  $\geq 90$   
 initial MacAdam  $\leq 3$  SDCM

**OPTICAL**

Variable

**ELECTRICAL**

phase-cut dim  
 220 - 240 V  
 system 6.0 W  
 Class 1

**PHYSICAL**

diameter 150 mm  
 height 100 mm  
 0.62 kg

[‘342168L9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.93	0.91	0.88
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.