



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Suspended luminaire for 48V tracks made from die-cast aluminium; track adapter with height adjustable cable system; surface White Matt wet painted; matt texture; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; 48 V; degree of protection IP20; Class 3; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Ceiling _____
 Track Suspended _____
 White Matt _____
 IP20 _____
 Interior _____
 470 lm _____
 CIE flux code: 95 97 99 100 _____
 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 L70 / 55000h _____
 initial MacAdam ≤ 2 SDCM _____

OPTICAL

Standard _____
 beam angle 32° _____


ELECTRICAL

DALI-2 _____
 48 V _____
 inset 7.0 W _____
 Class 3 _____

PHYSICAL

diameter 124 mm _____
 height 195 mm _____
 0.32 kg _____
 cable length 950-1200 mm _____
 adapter 175 mm _____
 incl. Strex 48 V track adapter _____

LIGHT DISTRIBUTION





CONE DIAGRAM

standard 32°

h (m)	E0° (lx)	ø (m)
1	1350	0.57
2	340	1.15
3	150	1.72
4	80	2.29
5	50	2.87

TRACK ACCESSORIES

Blank Cover 2m

Type	Colour	L·W·H (MM)	Item number
STREX system	Black	2000-18-3	911002B0
STREX system	White	2000-18-3	911002W0

Connector

Type	Colour	L·H (MM)	Item number
STREX system	White	105-18	90014196
STREX system	Black	105-18	90014197

DALI Selv Device

Type	L·W·H (MM)	Item number
STREX system	213-37-25	90019193

End Cap

Type	Colour	L·W·H (MM)	Item number
STREX system surface/suspended	White	26-2.5-29	90014147
STREX system surface/suspended	Black	26-2.5-29	90014148
STREX system recessed	White	37-10-27	90014149
STREX system recessed	Black	37-10-27	90014150
STREX system surface/suspended	Champagne	26-2.5-29	90014347
STREX system surface/suspended	Bronze	26-2.5-29	90014348

L-Connector

Type	Colour	L·W·H (MM)	Item number
STREX system surface/suspended	White	105-105-19	90014198
STREX system surface/suspended	Black	105-105-19	90014199
STREX system recessed	White	105-105-19	90014251
STREX system recessed	Black	105-105-19	90014252
STREX system surface/suspended	Champagne + Black	105-105-19	90014398
STREX system surface/suspended	Bronze + Black	105-105-19	90014399

L-Connector non-electrical

Type	Colour	L·W·H (MM)	Item number
STREX system recessed	White	105-105-19	90014256
STREX system recessed	Black	105-105-19	90014257
STREX system surface	White	105-105-19	90014258
STREX system surface	Black	105-105-19	90014259
STREX system surface	Champagne + Black	105-105-19	90014458
STREX system surface	Bronze + Black	105-105-19	90014459


Mounting Bracket
Type

STREX system | recessed

Item number

90014193

Power Feed
Type

STREX system

Colour

Black

L·W·H (MM)

112·18

Item number

90014154

Suspension Set
Type

STREX system | 1.5m | suspended

Colour

Stainless Steel

L·W·H (MM)

80·23·1500

Item number

90014160

STREX system | 3.0m | suspended

Stainless Steel

80·23·3000

90014161

STREX system | 1.5m | suspended

Black

80·23·1500

90014274

STREX system | 3.0m | suspended

Black

80·23·3000

90014275

T-Connector
Type

STREX system | surface

Colour

White

L·W·H (MM)

275·146·18

Item number

90014292

STREX system | surface

Black

275·146·18

90014293

X-Connector
Type

STREX system | surface

Colour

Black

L·W·H (MM)

275·275·18

Item number

90014294

STREX system | surface

White

275·275·18

90014295

ELECTRICAL ACCESSORIES

Ceiling Driver 100W
Type

STREX system | suspended

Colour

White

L·W·H (MM)

439·26·44

Item number

90014368

STREX system | suspended

Black

439·26·44

90014369

Ceiling Driver 150W
Type

STREX system | suspended

Colour

White

L·W·H (MM)

439·26·44

Item number

90014372

STREX system | suspended

Black

439·26·44

90014373

Driver
Type

STREX system | 100W

Voltage

48V

L·W·H (MM)

350·30·18

Item number

90218901

STREX system | 150W

48V

350·30·18

90218902

STREX system | 250W

48V

400·40·22

90218903

In Line Driver 100W
Type

STREX system | suspended

Colour

White

L·W·H (MM)

439·26·44

Item number

90014360

STREX system | suspended

Black

439·26·44

90014361

STREX system | surface

White

439·26·44

90014366

STREX system | surface

Black

439·26·44

90014367


In Line Driver 150W

Type	Colour	L·W·H (MM)	Item number
STREX system suspended	White	439·26·44	90014362
STREX system suspended	Black	439·26·44	90014363
STREX system surface	White	439·26·44	90014370
STREX system surface	Black	439·26·44	90014371

In Track Driver 100W

Type	Colour	L·W·H (MM)	Item number
STREX system surface	Black	438·16·18	90014143
STREX system surface	White	438·16·18	90014144
STREX system suspended	White	3000	90014157
STREX system suspended	Black	3000	90014174
STREX system surface	Black	468·26·29	90014176
STREX system surface	White	468·26·29	90014178
STREX system surface	Bronze + Black	468·26·29	90014376
STREX system surface	Champagne + Black	468·26·29	90014378

In Track Driver 250W

Type	Colour	L·W·H (MM)	Item number
STREX system surface	Black	408·16·18	90014145
STREX system surface	White	408·16·18	90014146
STREX system suspended	White	3000	90014158
STREX system suspended	Black	3000	90014175
STREX system surface	Black	438·26·29	90014177
STREX system surface	White	438·26·29	90014179
STREX system surface	Bronze + Black	438·26·29	90014377
STREX system surface	Champagne + Black	438·26·29	90014379

Power Feeder for Suspension

Colour	Item number
Black Texture	90018000

TRACKS
Track Profile 1m

Type	Colour	L·W·H (MM)	Item number
STREX system surface/suspended	White	1000·26·29	90014181
STREX system custom cut surface/suspended	White	200-999·26·29	90014181CC
STREX system surface/suspended	Black	1000·26·29	90014182
STREX system custom cut surface/suspended	Black	200-999·26·29	90014182CC
STREX system recessed	White	1000·37·33	90014187
STREX system custom cut recessed	White	200-999·37·33	90014187CC
STREX system recessed	Black	1000·37·33	90014188
STREX system custom cut recessed	Black	200-999·37·33	90014188CC


Track Profile 2m

Type	Colour	L-W-H (MM)	Item number
STREX system suspended indirect light	Black	2000-26-29	900140B5
STREX system custom cut suspended indirect light	Black	1000-1999-26-29	900140B5CC
STREX system suspended indirect light	White	2000-26-29	900140W5
STREX system custom cut suspended indirect light	White	1000-1999-26-29	900140W5CC
STREX system surface/suspended	White	2000-26-29	90014183
STREX system custom cut surface/suspended	White	1001-1999-26-29	90014183CC
STREX system surface/suspended	Black	2000-26-29	90014184
STREX system custom cut surface/suspended	Black	1001-1999-26-29	90014184CC
STREX system recessed	White	2000-37-33	90014189
STREX system custom cut recessed	White	1001-1999-37-33	90014189CC
STREX system recessed	Black	2000-37-33	90014190
STREX system custom cut recessed	Black	1001-1999-37-33	90014190CC
STREX system surface/suspended	Champagne	2000-26-29	90014383
STREX system custom cut surface/suspended	Champagne	1001-1999-26-29	90014383CC
STREX system surface/suspended	Bronze	2000-26-29	90014384
STREX system custom cut surface/suspended	Bronze	1001-1999-26-29	90014384CC

Track Profile 3m

Type	Colour	L-W-H (MM)	Item number
STREX system surface/suspended	White	3000-26-29	90014185
STREX system custom cut surface/suspended	White	2001-2999-26-29	90014185CC
STREX system surface/suspended	Black	3000-26-29	90014186
STREX system custom cut surface/suspended	Black	2001-2999-26-29	90014186CC
STREX system recessed	White	3000-37-33	90014191
STREX system custom cut recessed	White	2001-2999-37-33	90014191CC
STREX system recessed	Black	3000-37-33	90014192
STREX system custom cut recessed	Black	2001-2999-37-33	90014192CC
STREX system suspended indirect light	Black	3000-26-29	900141B5
STREX system custom cut suspended indirect light	Black	2001-2999-26-29	900141B5CC
STREX system suspended indirect light	White	3000-26-29	900141W5
STREX system custom cut suspended indirect light	White	2001-2999-26-29	900141W5CC
STREX system surface/suspended	Champagne	3000-26-29	90014385
STREX system custom cut surface/suspended	Champagne	2001-2999-26-29	90014385CC
STREX system surface/suspended	Bronze	3000-26-29	90014386
STREX system custom cut surface/suspended	Bronze	2001-2999-26-29	90014386CC