



WEVER & DUCRÉ
LIGHTING

RAY 1.0 LED

186764W2

GENERAL

Ceiling

Surface

White Matt

RAL 9003^a

IP20

Interior

675 lm

LED

2700 K

CRI ≥ 90

L70 / 50000 h

3-step binning

OPTICAL

Flood

Beam angle 21°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.9 W

Class 1

Safety distance 0.3 m

PHYSICAL

Diameter 114 mm

Height 100 mm

0.7 kg

^a Color may deviate slightly due to production conditions.


Project

Type


Notes

Quantity

Date



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9003; optional single inner cover available; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; light source replaceable by an authorized professional;






WEVER & DUCRÉ
LIGHTING

RAY 1.0 LED

186764W2

LIGHT DISTRIBUTION



Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.95	0.9	0.85	0.8	0.76
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Single Inner Cover

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
RAY max. 10W	Black	Ø67·54	911041B1
RAY max. 10W	Gold	Ø67·54	911041G1
RAY max. 10W	White	Ø67·54	911041W1