




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Round shape wall surface mounted luminaire with diffuse light; aluminium base in White Matt wet painted; matt texture; aluminium shade; surface Feel Jade wet painted; matt texture; NCS S 2005 - G90Y; white opal glass handblown; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; CRI (Colour Rendering Index)  $\geq 90$ ; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



**GENERAL**

Wall \_\_\_\_\_

Surface \_\_\_\_\_

Feel Jade \_\_\_\_\_

NCS S 2005 - G90Y <sup>a</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

465 lm \_\_\_\_\_

CIE flux code: 18 43 71 50 100 \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

**OPTICAL**

Opal \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 10.1 W \_\_\_\_\_

Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 700 mm \_\_\_\_\_

height 94 mm \_\_\_\_\_

2.09 kg \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.



**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.