



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



**GENERAL**

Ceiling \_\_\_\_\_  
 Track \_\_\_\_\_  
 rotation 310 ° \_\_\_\_\_  
 Black Matt + Gold \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 280 lm \_\_\_\_\_  
 CIE flux code: 65 94 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L80 / 60000h \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Opal \_\_\_\_\_

**ELECTRICAL**


phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 6.6 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

length 94 mm \_\_\_\_\_  
 width 50 mm \_\_\_\_\_  
 height 65 mm \_\_\_\_\_  
 0.33 kg \_\_\_\_\_  
 adapter 75 mm \_\_\_\_\_  
 incl. 1-phase track adapter \_\_\_\_\_



Downlight made from die-cast aluminium incl. 1-phase track adapter; opal PMMA cover; housing Black Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; CRI (Colour Rendering Index) ≥ 90; 310° rotatable; degree of protection IP20; Class 1; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



[173284K5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.


**MOUNTING ACCESSORIES**
**Adjustable Corner**

Type	Colour	L·W·H (MM)	Item number
1-phase track	Black	81·81·20	90014041
1-phase track	White	81·81·20	90014042

**X-Connector**

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	145·145·20	90014049
1-phase track	Black	145·145·20	90014050

**TRACK ACCESSORIES**
**Coverplate End Feed**

Type	Colour	L·W (MM)	Item number
1-phase track   recessed	White	75·50	90014124
1-phase track   recessed	Black	75·50	90014125

**Coverplate I/L/T/X**

Type	Colour	L·W (MM)	Item number
1-phase track   recessed	White	100·100	90014126
1-phase track   recessed	Black	100·100	90014127

**End Cap**

Type	Colour	L·W·H (MM)	Item number
1-phase track   left/right	White	24·30·20	90014028
1-phase track   left/right	Black	24·30·20	90014029

**End Feed | left**

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	88·30·20	90014018
1-phase track	Black	88·30·20	90014019

**End Feed | right**

Type	Colour	L·W·H (MM)	Item number
1-phase track	White	88·30·20	90014020
1-phase track	Black	88·30·20	90014021

**L-Connector**

Type	Colour	L·W·H (MM)	Item number
1-phase track   left	White	88·55·20	90014024
1-phase track   left	Black	88·55·20	90014025
1-phase track   right	White	88·55·20	90014026
1-phase track   right	Black	88·55·20	90014027

**Middle Feed**

Type	Colour	L·W·H (MM)	Item number
1-phase track   straight	White	145·30·20	90014036
1-phase track   straight	Black	145·30·20	90014037

**Mounting Bracket**

Type	L·W·H (MM)	Item number
1-phase track   recessed	35·59·35	90014100


**Straight Connector**

Type	Colour	L-H (MM)	Item number
1-phase track   straight	White	65-17	90014022
1-phase track   straight	Black	65-17	90014023

**Suspension Set 1.5m**

Type	Colour	Ø-H (MM)	Item number
1-phase track   suspended	White	29-1500	90014101
1-phase track   suspended	Black	29-1500	90014102

**Suspension Set 3.0m**

Type	Colour	Ø-H (MM)	Item number
1-phase track   suspended	White	29-3000	90014103
1-phase track   suspended	Black	29-3000	90014104

**T-Connector 1.0**

Type	Colour	L-W-H (MM)	Item number
1-phase track	White	145-55-20	90014010
1-phase track	Black	145-55-20	90014011

**T-Connector 2.0**

Type	Colour	L-W-H (MM)	Item number
1-phase track	White	145-55-20	90014012
1-phase track	Black	145-55-20	90014013

**T-Connector 3.0**

Type	Colour	L-W-H (MM)	Item number
1-phase track	White	145-55-20	90014014
1-phase track	Black	145-55-20	90014015

**T-Connector 4.0**

Type	Colour	L-W-H (MM)	Item number
1-phase track	White	145-55-20	90014016
1-phase track	Black	145-55-20	90014017

**Track Adapter 1.0**

Type	Colour	L-H (MM)	Item number
1-phase track	Black	85-45	90014043
1-phase track	White	85-45	90014044

**TRACKS**
**Track Profile 1m**

Type	Colour	L-W-H (MM)	Item number
1-phase track   surface/suspended	White	1000-30-20	90014001
1-phase track   surface/suspended	Black	1000-30-20	90014007
1-phase track   recessed	White	1000-50-20	90014118
1-phase track   recessed	Black	1000-50-20	90014119


**Track Profile 2m**

Type	Colour	L·W·H (MM)	Item number
1-phase track   surface/suspended	White	2000·30·20	90014002
1-phase track   surface/suspended	Black	2000·30·20	90014008
1-phase track   recessed	White	2000·50·20	90014120
1-phase track   recessed	Black	2000·50·20	90014121

**Track Profile 3m**

Type	Colour	L·W·H (MM)	Item number
1-phase track   surface/suspended	White	3000·30·20	90014003
1-phase track   surface/suspended	Black	3000·30·20	90014009
1-phase track   recessed	White	3000·50·20	90014122
1-phase track   recessed	Black	3000·50·20	90014123