

# PROJECT TYPE NOTES QUANTITY DATE



Ceiling surface spotlight made from die-cast aluminium; with rectangular base; surface White Matt + Gold; powder coated; matt texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq$  90; beam angle 23°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

# 330 26

 $^{/}$  26

130 26

## GENERAL

Ceiling / Wall	
Surface	
tilt max 90 °	
rotation 350 °	
White Matt + Gold	
IP20	
Interior	
410 lm	
CIE flux code: 90 98 100 100	
100	

#### LED

2700 K
$CRI \ge 90$
L80 / 50000h
initial MacAdam ≤ 2 SDCM

### OPTICAL

Standard
beam angle 23°

#### ELECTRICAL

phase-cut dim	
220 - 240 V	
system 13.8 W	
Class 1	

#### PHYSICAL

ength 330 mm
width 26 mm
neight 130 mm
0.35 kg

['159144J3'] The technical data represent rated values for an ambient temperature of  $25^{\circ}$ C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



159144J3





Maintenance Factor

**MICK 1.0** 

159144J3



#### **Maintenance Factor**

MF

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1
MF LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Mainter	nance Factor	

RSMF<sup>a</sup>

LLMF

Lamp Lumens Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor LSF Lamp Survival Factor <sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

['159144J3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply. © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com