

PIRRO SPOT SURFACE 4.0

151464K3



PROJECT

TYPE

NOTES

QUANTITY

DATE











Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing Black Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; degree of protection IP20; Class 1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^{\circ} \leq 1500$ cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
Surface
Black Matt + Gold
IP20
Interior
1470 lm
CIE flux code: 99 100 100 100
100

LED

2700 K
CRI ≥ 90
L70 / 55000h
initial MacAdam ≤ 2 SDCM

OPTICAL


Standard	
beam angle 32°	

ELECTRICAL

phase-cut dim	
220 - 240 V	
system 19.3 W	
Class 1	

PHYSICAL

length 182 mm	
width 50 mm	
height 80 mm	
0.48 kg	





PIRRO SPOT SURFACE 4.0

151464K3



MOUNTING ACCESSORIES

1.0 Ceiling Bas					
	_	D	 C-:1	1 ^	-

Туре	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	754-51-12	90052072
PIRRO SYSTEM	Black	754.51.12	90052073
PIRRO SYSTEM	Gold	754-51-12	90052074

2.0 Ceiling Base

Туре	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	1150-51-12	90052075
PIRRO SYSTEM	Black	1150-51-12	90052076
PIRRO SYSTEM	Gold	1150-51-12	90052077

OPTICAL ACCESSORIES

Honey	vcomb	Louver
HOHE	COIIID	Louvei

Colour Ø (MM) Item number
Black 29 90051131
Black 25