



**PROJECT**

---

**TYPE**

---

**NOTES**


---

**QUANTITY**

---

**DATE**

---



Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing Black Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; degree of protection IP20; Class 1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500$  cd/m<sup>2</sup>; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**GENERAL**

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Black Matt \_\_\_\_\_  
 RAL 9005 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 1340 lm \_\_\_\_\_  
 CIE flux code: 99 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L70 / 55000h \_\_\_\_\_  
 initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_  
 beam angle  $32^\circ$  \_\_\_\_\_


**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 19.3 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

length 182 mm \_\_\_\_\_  
 width 50 mm \_\_\_\_\_  
 height 80 mm \_\_\_\_\_  
 0.48 kg \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.



[151464B5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

**MOUNTING ACCESSORIES****1.0 Ceiling Base**

Type	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	754-51-12	90052072
PIRRO SYSTEM	Black	754-51-12	90052073
PIRRO SYSTEM	Gold	754-51-12	90052074

**2.0 Ceiling Base**

Type	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	1150-51-12	90052075
PIRRO SYSTEM	Black	1150-51-12	90052076
PIRRO SYSTEM	Gold	1150-51-12	90052077

**OPTICAL ACCESSORIES****Honeycomb Louver**

Type	Colour	Ø (MM)	Item number
BLIEK PETIT   CENO   LECA   PIRRO	Black	29	90051131