

PIRRO SPOT SURFACE 4.0

151464B3

PROJECT

TYPE

NOTES

QUANTITY

DATE











Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing Black Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; degree of protection IP20; Class 1; UGR \leq 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° \leq 1500 cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
Surface
Black Matt
RAL 9005 ^a
IP20
Interior
1290 lm
CIE flux code: 99 100 100 100
100

LED

2700 K	
CRI ≥ 90	
L70 / 55000h	
initial MacAdam ≤ 2 SDCM	

OPTICAL

Standard	
beam angle 32°	


ELECTRICAL

phase-cut dim
220 - 240 V
system 19.3 W
Class 1

PHYSICAL

length 182 mm	
width 50 mm	
height 80 mm	
0.48 kg	

^a Colour may deviate slightly due to production conditions.





PIRRO SPOT SURFACE 4.0

151464B3



MOUNTING ACCESSORIES

1.0 Ceiling B	ase
---------------	-----

Туре	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	754.51.12	90052072
PIRRO SYSTEM	Black	754-51-12	90052073
PIRRO SYSTEM	Gold	754.51.12	90052074

2.0 Ceiling Base

Туре	Colour	L·W·H (MM)	Item number
PIRRO SYSTEM	White	1150-51-12	90052075
PIRRO SYSTEM	Black	1150-51-12	90052076
PIRRO SYSTEM	Gold	1150-51-12	90052077

OPTICAL ACCESSORIES

Honeycomb Louver

BLIEK PETIT CENO LECA PIRRO Black	Ø (MM)	Item number
DELEKT ETTT CENTO ELOK TIMES	29	90051131