

## PIRRO SPOT SURFACE 1.0

151164B5

回缆张回
3200

**PROJECT** 

**TYPE** 

**NOTES** 

QUANTITY

DATE











Squared ceiling surface mounted downlight made from die-cast aluminium; housing Black Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; degree of protection IP20; Class 1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^{\circ} \leq 1500$  cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

#### **GENERAL**

Ceiling
Surface
Black Matt
RAL 9005 <sup>a</sup>
IP20
Interior
355 lm
CIE flux code: 99 100 100 100
100

## LED

3000 K	
CRI ≥ 90	
L70 / 55000h	
initial MacAdam ≤ 2 SDCM	

#### **OPTICAL**

Standard	
beam angle 32°	

### **ELECTRICAL**

phase-cut dim	
220 - 240 V	
system 5.5 W	
Class 1	

## **PHYSICAL**

length 50 mm	
width 50 mm	
height 80 mm	
0.2 kg	

<sup>&</sup>lt;sup>a</sup> Colour may deviate slightly due to production conditions.





# PIRRO SPOT SURFACE 1.0

151164B5



## **Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.9	0.88	0.85	0.83	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor	

<sup>&</sup>lt;sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## **OPTICAL ACCESSORIES**

## **Honeycomb Louver**

Туре	Colour	Ø (MM)	Item number
BLIEK PETIT   CENO   LECA   PIRRO	Black	29	90051131