

PIRRO SPOT SURFACE 6.0


151664J3

PROJECT		
ТҮРЕ		
NOTES		
QUANTITY		
DATE		





Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing White Matt powder coated; matt texture; with reflector in Gold wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; degree of protection IP20; Class 1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^{\circ} \leq 1500$ cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Ceiling
Surface
White Matt + Gold
IP20
Interior
2000 lm
CIE flux code: 99 100 100 100
100

LED

2700 K CRI \geq 90 L70 / 55000h initial MacAdam \leq 2 SDCM

OPTICAL

Standard beam angle 32°

ELECTRICAL

phase-cut dim	
220 - 240 V	
system 28.3 W	
Class 1	

PHYSICAL

length 270 mm	
width 50 mm	
height 80 mm	
0.8 kg	

['151664J3'] The technical data represent rated values for an ambient temperature of 25° C. The data values for the luminous flux are initially subject to a tolerance of +/-10%, and those for the electrical connected load are initially subject to a tolerance of +/-10%, and those for the colour temperature are initially subject to a tolerance of +/-150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



PIRRO SPOT SURFACE 6.0

151664J3

Mainter	nance Factor					
Operati	ing Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF		0.9	0.88	0.85	0.83	0.81
LSF		1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenar	nce Factor	
MF	Maintenance Factor	LLMF Lamp Lumens Maintenance Fac		nce Factor		
l MF ^a	Luminaire Maintenance Factor		LSF Lamp Survival Factor			

OPTICAL ACCESSORIES

Colour	Ø (MM)	Item number
Black	29	90051131

['151664J3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply. © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com