

## PIRRO SPOT SURFACE 6.0

151664E5



#### **PROJECT**

**TYPE** 

**NOTES** 

QUANTITY

DATE











Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing White Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq$  2 SDCM; CRI  $\geq$  90; degree of protection IP20; Class 1; UGR  $\leq$  13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65°  $\leq$  1500 cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

## **GENERAL**

Ceiling
Surface
White Matt + Black Matt
IP20
Interior
2020 lm
CIE flux code: 99 100 100 100
100

## LED

3000 K
CRI ≥ 90
L70 / 55000h
initial MacAdam ≤ 2 SDCM

#### **OPTICAL**


Standard	
beam angle 32°	

## **ELECTRICAL**

phase-cut dim
220 - 240 V
system 28.3 W
Class 1

## **PHYSICAL**

length 270 mm	
width 50 mm	
height 80 mm	
0.8 kg	





# PIRRO SPOT SURFACE 6.0

151664E5



## **Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.9	0.88	0.85	0.83	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>&</sup>lt;sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## **OPTICAL ACCESSORIES**

Honey	comb	Louver
-------	------	--------

Туре	Colour	Ø (MM)	Item number
BLIEK PETIT   CENO   LECA   PIRRO	Black	29	90051131