

PIRRO SPOT SURFACE 6.0

151664E3

回缆床回
75/26/2

PROJECT

TYPE

NOTES

QUANTITY

DATE











Rectangular ceiling surface mounted downlight made from die-cast aluminium; housing White Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; degree of protection IP20; Class 1; UGR \leq 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° \leq 1500 cd/m²; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

GENERAL

Ceiling
Surface
White Matt + Black Matt
IP20
Interior
1920 lm
CIE flux code: 99 100 100 100
100
Interior 1920 lm CIE flux code: 99 100 100 100

LED

2700 K	
CRI ≥ 90	
L70 / 55000h	
initial MacAdam ≤ 2 SDCM	
	_

OPTICAL


Standard	
beam angle 32°	

ELECTRICAL

phase-cut dim	
220 - 240 V	
system 28.3 W	
Class 1	
Class 1	

PHYSICAL

length 270 mm	
width 50 mm	
height 80 mm	
0.8 kg	





PIRRO SPOT SURFACE 6.0

151664E3



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.9	0.88	0.85	0.83	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL ACCESSORIES

Honey	comb	Louver
-------	------	--------

Туре	Colour	Ø (MM)	Item number
BLIEK PETIT CENO LECA PIRRO	Black	29	90051131