



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



GENERAL

Floor _____
 Recessed _____
 Inox _____
 IP67 _____
 IK08 _____
 Exterior _____
 995 lm _____
 CIE flux code: 33 55 77 0 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 L70 / 55000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Wide _____
 beam angle 44° _____
 UGR < 10 _____
 ≥65° < 1500 cd/m² _____

ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 11.9 W _____
 Class 2 _____

PHYSICAL


diameter 120 mm _____
 height 113 mm _____
 1.01 kg _____

CUTOUT

recessed depth 120 mm _____



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 120 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 44°; degree of protection IP67; Class 2; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[75136815] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.91	0.81	0.73	0.66	0.59
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

Ground Housing

Type	Ø·H (MM)	Item number
MAP 1.2 CHART 1.2 MAP ASYM 1.2 CHART ASYM 1.2	185-150	90012203