



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Floor
 Recessed
 Inox
 IP67
 IK08
 Exterior
 310 lm
 CIE flux code: 25 48 71 0 100

LED

3000 K
 CRI ≥ 90
 L70 / 55000h
 initial MacAdam ≤ 3 SDCM

OPTICAL

Wide
 beam angle 43°
 UGR < 10
 ≥65° < 1500 cd/m²

ELECTRICAL

phase-cut dim
 220 - 240 V
 5.0 W
 Class 2

PHYSICAL


diameter 55 mm
 height 95 mm
 0.38 kg

CUTOUT

recessed depth 100 mm



Round floor recessed luminaire made from stainless steel and glass; surface Inox; recessed depth 100 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 43°; degree of protection IP67; Class 2; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[75116815] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



MOUNTING ACCESSORIES

Ground Housing

Type

MAP 0.6 | CHART 0.6 | BLINK TRIM | TRIMLESS

Ø-H (MM)

132.105

Item number

90012201