



**PROJECT**

---

**TYPE**

---

**NOTES**

---

**QUANTITY**

---

**DATE**

---



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9003; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**GENERAL**

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 RAL 9003 <sup>a</sup> \_\_\_\_\_  
 IP65 \_\_\_\_\_  
 Exterior \_\_\_\_\_  
 670 lm \_\_\_\_\_  
 CIE flux code: 94 99 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 initial MacAdam  $\leq 3$  SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_  
 beam angle 21° \_\_\_\_\_


**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 8.0 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 114 mm \_\_\_\_\_  
 height 100 mm \_\_\_\_\_  
 0.63 kg \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.



[735458W3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**OPTICAL ACCESSORIES**

**Single Inner Cover**

Type	Colour	Ø-H (MM)	Item number
RAY   max. 10W	Anthracite Grey	67-54	911041A1
RAY   max. 10W	Black	67-54	911041B1
RAY   max. 10W	Dark Grey Texture	67-54	911041D1
RAY   max. 10W	White	67-54	911041W1