



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Ceiling
 Surface
 Grey Texture
 RAL 9007 ^a
 IP65
 Exterior
 700 lm
 CIE flux code: 95 99 100 100
 100

LED

3000 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

OPTICAL

Standard
 beam angle 21°

ELECTRICAL

phase-cut dim
 220 - 240 V
 system 8.0 W
 Class 1


PHYSICAL

diameter 114 mm
 height 100 mm
 0.63 kg



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

^a Colour may deviate slightly due to production conditions.





OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Ø-H (MM)	Item number
RAY max. 10W	Anthracite Grey	67-54	911041A1
RAY max. 10W	Black	67-54	911041B1
RAY max. 10W	Dark Grey Texture	67-54	911041D1
RAY max. 10W	White	67-54	911041W1