



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling _____

Surface _____

Grey Texture _____

RAL 9007 ^a _____

IP65 _____

Exterior _____

CIE flux code: 95 99 100 100 _____

100 _____

LED

3000 K _____

CRI ≥ 90 _____

initial MacAdam ≤ 3 SDCM _____

OPTICAL

Standard _____

beam angle 21° _____

ELECTRICAL

phase-cut dim _____

220 - 240 V _____

8.0 W _____

Class 1 _____


PHYSICAL

diameter 114 mm _____

height 100 mm _____

0.63 kg _____

^a Colour may deviate slightly due to production conditions.





OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Ø-H (MM)	Item number
RAY max. 10W	Anthracite Grey	67-54	911041A1
RAY max. 10W	Black	67-54	911041B1
RAY max. 10W	Dark Grey Texture	67-54	911041D1
RAY max. 10W	White	67-54	911041W1