



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Ceiling _____
 Surface _____
 Anthracite Grey _____
 RAL 7016 ^a _____
 IP65 _____
 Exterior _____
 700 lm _____
 CIE flux code: 96 100 100 100 _____
 100 _____

LED

3000 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Standard _____
 beam angle 21° _____

ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 8.0 W _____
 Class 1 _____


PHYSICAL

diameter 114 mm _____
 height 100 mm _____
 0.63 kg _____



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

^a Colour may deviate slightly due to production conditions.





OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Ø-H (MM)	Item number
RAY max. 10W	Anthracite Grey	67-54	911041A1
RAY max. 10W	Black	67-54	911041B1
RAY max. 10W	Dark Grey Texture	67-54	911041D1
RAY max. 10W	White	67-54	911041W1