



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**GENERAL**

Ceiling \_\_\_\_\_

Surface \_\_\_\_\_

Anthracite Grey \_\_\_\_\_

RAL 7016 <sup>a</sup> \_\_\_\_\_

IP65 \_\_\_\_\_

Exterior \_\_\_\_\_

CIE flux code: 96 100 100 100 \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

initial MacAdam  $\leq 3$  SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_

beam angle 21° \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

8.0 W \_\_\_\_\_

Class 1 \_\_\_\_\_


**PHYSICAL**

diameter 114 mm \_\_\_\_\_

height 100 mm \_\_\_\_\_

0.63 kg \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.





**OPTICAL ACCESSORIES**

**Single Inner Cover**

Type	Colour	Ø-H (MM)	Item number
RAY   max. 10W	Anthracite Grey	67-54	911041A1
RAY   max. 10W	Black	67-54	911041B1
RAY   max. 10W	Dark Grey Texture	67-54	911041D1
RAY   max. 10W	White	67-54	911041W1