



PROJECT

TYPE

NOTES

QUANTITY

DATE



IP65



GENERAL

Ceiling _____
Surface _____
Anthracite Grey _____
RAL 7016 ^a _____
IP65 _____
Exterior _____
CIE flux code: 96 100 100 100 _____
100 _____

LED

2700 K _____
CRI ≥ 90 _____
initial MacAdam ≤ 3 SDCM _____

OPTICAL

Standard _____
beam angle 21° _____

ELECTRICAL


phase-cut dim _____
220 - 240 V _____
8.0 W _____
Class 1 _____

PHYSICAL

diameter 114 mm _____
height 100 mm _____
0.63 kg _____

Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

^a Colour may deviate slightly due to production conditions.



[735458A3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



OPTICAL ACCESSORIES

Single Inner Cover

| Type | Colour | Ø-H (MM) | Item number |
|----------------|-------------------|----------|-------------|
| RAY max. 10W | Anthracite Grey | 67-54 | 911041A1 |
| RAY max. 10W | Black | 67-54 | 911041B1 |
| RAY max. 10W | Dark Grey Texture | 67-54 | 911041D1 |
| RAY max. 10W | White | 67-54 | 911041W1 |