



**PROJECT**

---

**TYPE**

---

**NOTES**

---

**QUANTITY**

---

**DATE**

---



**GENERAL**

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Anthracite Grey \_\_\_\_\_  
 RAL 7016 <sup>a</sup> \_\_\_\_\_  
 IP65 \_\_\_\_\_  
 Exterior \_\_\_\_\_  
 670 lm \_\_\_\_\_  
 CIE flux code: 96 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_  
 beam angle 21° \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 8.0 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_


**PHYSICAL**

diameter 114 mm \_\_\_\_\_  
 height 100 mm \_\_\_\_\_  
 0.63 kg \_\_\_\_\_



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class 1; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

<sup>a</sup> Colour may deviate slightly due to production conditions.





**OPTICAL ACCESSORIES**

**Single Inner Cover**

Type	Colour	Ø-H (MM)	Item number
RAY   max. 10W	Anthracite Grey	67-54	911041A1
RAY   max. 10W	Black	67-54	911041B1
RAY   max. 10W	Dark Grey Texture	67-54	911041D1
RAY   max. 10W	White	67-54	911041W1