



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



## GENERAL

Wall \_\_\_\_\_  
Surface \_\_\_\_\_  
Champagne \_\_\_\_\_  
IP20 \_\_\_\_\_  
Interior \_\_\_\_\_  
total 650 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_  
CRI  $\geq$  90 \_\_\_\_\_  
initial MacAdam  $\leq$  3 SDCM \_\_\_\_\_

## OPTICAL


Variable \_\_\_\_\_

## ELECTRICAL

phase-cut dim \_\_\_\_\_  
220 - 240 V \_\_\_\_\_  
system 11.0 W \_\_\_\_\_  
Class 1 \_\_\_\_\_

## PHYSICAL

diameter 150 mm \_\_\_\_\_  
height 160 mm \_\_\_\_\_  
0.85 kg \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne; direct/indirect light distribution; PCB 3-step binning; phase-cut dim; light colour 2700 K; CRI  $\geq$  90; 220 - 240 V; degree of protection IP20; Class 1; driver included; inclusive flaps for adjustable beam angle; light source replaceable by an authorized professional;

