



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



**GENERAL**

Wall  
 Surface  
 Champagne  
 IP20  
 Interior  
 370 lm

**LED**

3000 K  
 CRI  $\geq$  90  
 initial MacAdam  $\leq$  3 SDCM

**OPTICAL**


Variable

**ELECTRICAL**


phase-cut dim  
 220 - 240 V  
 system 6.0 W  
 Class 1

**PHYSICAL**

diameter 150 mm  
 height 100 mm  
 0.62 kg



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; CRI  $\geq$  90; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[‘342168M5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.