



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



**GENERAL**

Wall \_\_\_\_\_  
 Surface \_\_\_\_\_  
 Champagne \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**OPTICAL**

Variable \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 6.0 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

diameter 150 mm \_\_\_\_\_  
 height 100 mm \_\_\_\_\_  
 0.62 kg \_\_\_\_\_



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 3000 K; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

