



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



GENERAL

Wall _____
 Surface _____
 Champagne _____
 IP20 _____
 Interior _____

LED

2700 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Variable _____

ELECTRICAL


phase-cut dim _____
 220 - 240 V _____
 6.0 W _____
 Class 1 _____

PHYSICAL

diameter 150 mm _____
 height 100 mm _____
 0.62 kg _____



Cylindrical wall surface mounted luminaire made from aluminium; surface Champagne; direct light distribution; PCB 3-step binning; phase-cut dim; light colour 2700 K; CRI ≥ 90; 220 - 240 V; degree of protection IP20; Class 1; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



[‘342168M3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.