



**PROJECT**

**TYPE**

**NOTES**

**QUANTITY**

**DATE**



Tubular ceiling suspended luminaire made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; inclusive adjustable cable suspension max. 2500mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; 220 - 240 V; beam angle 33°; degree of protection IP20; Class 2; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**LUMINAIRE**

Ceiling  
Suspended  
Black Matt  
RAL 9011<sup>a</sup>  
IP20  
Interior  
460 lm

**LED Module**

3000 K  
CRI  $\geq 90$   
L80 / 50000h  
 $\leq 2$  SDCM (initial MacAdam)

**Optical**

Medium (standard)  
beam angle 33°  
CIE flux code: 91 97 99 100 100


**Electrical**

phase-cut dim  
220 - 240 V  
system 8.5 W  
Class II

**Physical**

diameter 26 mm  
height 300 mm  
0.26 kg

**LIGHT DISTRIBUTION**



[279264B5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



## CONE DIAGRAM

medium (standard) 34°

h (m)	E0° (lx)	ø (m)
1	1000	0.62
2	250	1.23
3	110	1.85
4	60	2.47
5	40	3.08

## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.93	0.9	0.88
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor

RSMF<sup>a</sup> Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.