



PROJECT

TYPE


NOTES

QUANTITY

DATE



48V track downlight made from die-cast aluminium; cylindrical shape; for surface and suspended tracks; adapter in Black Matt; surface housing with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; 48 V; degree of protection IP20; Class 3; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



GENERAL

Ceiling _____
 Track _____
 Black Matt _____
 Adapter Black Matt _____
 RAL 9005 ^a _____
 Housing + Inner Reflector _____
 Champagne + Black Matt _____
 IP20 _____
 Interior _____
 440 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 2 SDCM _____

OPTICAL

Standard _____
 beam angle 25° _____

ELECTRICAL

DALI-2 _____
 48 V _____
 inset 7.0 W _____
 Class 3 _____

PHYSICAL

diameter 70 mm _____
 height 82 mm _____
 0.16 kg _____
 adapter 171 mm _____
 incl. Strex 48 V track adapter _____

^a Colour may deviate slightly due to production conditions.

[‘258265BH3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.


TRACK ACCESSORIES
Blank Cover 2m

| Type | Colour | L·W·H (MM) | Item number |
|--------------|--------|------------|-------------|
| STREX system | Black | 2000-18-3 | 911002B0 |
| STREX system | White | 2000-18-3 | 911002W0 |

Connector

| Type | Colour | L·H (MM) | Item number |
|--------------|--------|----------|-------------|
| STREX system | White | 105-18 | 90014196 |
| STREX system | Black | 105-18 | 90014197 |

DALI Selv Device

| Type | L·W·H (MM) | Item number |
|--------------|------------|-------------|
| STREX system | 213-37-25 | 90019193 |

End Cap

| Type | Colour | L·W·H (MM) | Item number |
|----------------------------------|-----------|------------|-------------|
| STREX system surface/suspended | White | 26-2.5-29 | 90014147 |
| STREX system surface/suspended | Black | 26-2.5-29 | 90014148 |
| STREX system surface/suspended | Champagne | 26-2.5-29 | 90014347 |
| STREX system surface/suspended | Bronze | 26-2.5-29 | 90014348 |

L-Connector

| Type | Colour | L·W·H (MM) | Item number |
|----------------------------------|-------------------|------------|-------------|
| STREX system surface/suspended | White | 105-105-19 | 90014198 |
| STREX system surface/suspended | Black | 105-105-19 | 90014199 |
| STREX system surface/suspended | Champagne + Black | 105-105-19 | 90014398 |
| STREX system surface/suspended | Bronze + Black | 105-105-19 | 90014399 |

L-Connector non-electrical

| Type | Colour | L·W·H (MM) | Item number |
|------------------------|-------------------|------------|-------------|
| STREX system surface | White | 105-105-19 | 90014258 |
| STREX system surface | Black | 105-105-19 | 90014259 |
| STREX system surface | Champagne + Black | 105-105-19 | 90014458 |
| STREX system surface | Bronze + Black | 105-105-19 | 90014459 |

Power Feed

| Type | Colour | L·H (MM) | Item number |
|--------------|--------|----------|-------------|
| STREX system | Black | 112-18 | 90014154 |

Suspension Set

| Type | Colour | L·W·H (MM) | Item number |
|---------------------------------|-----------------|------------|-------------|
| STREX system 1.5m suspended | Stainless Steel | 80-23-1500 | 90014160 |
| STREX system 3.0m suspended | Stainless Steel | 80-23-3000 | 90014161 |
| STREX system 1.5m suspended | Black | 80-23-1500 | 90014274 |
| STREX system 3.0m suspended | Black | 80-23-3000 | 90014275 |

T-Connector

| Type | Colour | L·W·H (MM) | Item number |
|------------------------|--------|------------|-------------|
| STREX system surface | White | 275-146-18 | 90014292 |
| STREX system surface | Black | 275-146-18 | 90014293 |

258265BH3

Wireless Casambi Control

| Type | Colour | L-H (MM) | Item number |
|--------------|--------|----------|-------------|
| STREX system | White | 143-58 | 90014155 |
| STREX system | Black | 143-58 | 90014156 |

X-Connector

| Type | Colour | L-W-H (MM) | Item number |
|------------------------|--------|------------|-------------|
| STREX system surface | Black | 275-275-18 | 90014294 |
| STREX system surface | White | 275-275-18 | 90014295 |

ELECTRICAL ACCESSORIES
Ceiling Driver 100W

| Type | Colour | L-W-H (MM) | Item number |
|--------------------------|--------|------------|-------------|
| STREX system suspended | White | 439-26-44 | 90014368 |
| STREX system suspended | Black | 439-26-44 | 90014369 |

Ceiling Driver 150W

| Type | Colour | L-W-H (MM) | Item number |
|--------------------------|--------|------------|-------------|
| STREX system suspended | White | 439-26-44 | 90014372 |
| STREX system suspended | Black | 439-26-44 | 90014373 |

Driver

| Type | Voltage | L-W-H (MM) | Item number |
|---------------------|---------|------------|-------------|
| STREX system 100W | 48V | 350-30-18 | 90218901 |
| STREX system 150W | 48V | 350-30-18 | 90218902 |
| STREX system 250W | 48V | 400-40-22 | 90218903 |

In Line Driver 100W

| Type | Colour | L-W-H (MM) | Item number |
|--------------------------|--------|------------|-------------|
| STREX system suspended | White | 439-26-44 | 90014360 |
| STREX system suspended | Black | 439-26-44 | 90014361 |

In Line Driver 150W

| Type | Colour | L-W-H (MM) | Item number |
|--------------------------|--------|------------|-------------|
| STREX system suspended | White | 439-26-44 | 90014362 |
| STREX system suspended | Black | 439-26-44 | 90014363 |

In Track Driver 100W

| Type | Colour | L-W-H (MM) | Item number |
|--------------------------|-------------------|------------|-------------|
| STREX system surface | Black | 438-16-18 | 90014143 |
| STREX system surface | White | 438-16-18 | 90014144 |
| STREX system suspended | White | 3000 | 90014157 |
| STREX system suspended | Black | 3000 | 90014174 |
| STREX system surface | Black | 468-26-29 | 90014176 |
| STREX system surface | White | 468-26-29 | 90014178 |
| STREX system surface | Bronze + Black | 468-26-29 | 90014376 |
| STREX system surface | Champagne + Black | 468-26-29 | 90014378 |


In Track Driver 250W

| Type | Colour | L·W·H (MM) | Item number |
|--------------------------|-------------------|------------|-------------|
| STREX system surface | Black | 408-16-18 | 90014145 |
| STREX system surface | White | 408-16-18 | 90014146 |
| STREX system suspended | White | 3000 | 90014158 |
| STREX system suspended | Black | 3000 | 90014175 |
| STREX system surface | Black | 438-26-29 | 90014177 |
| STREX system surface | White | 438-26-29 | 90014179 |
| STREX system surface | Bronze + Black | 438-26-29 | 90014377 |
| STREX system surface | Champagne + Black | 438-26-29 | 90014379 |

Power Feeder for Suspension

| Colour | Item number |
|---------------|-------------|
| Black Texture | 90018000 |

TRACKS
Track Profile 1m

| Type | Colour | L·W·H (MM) | Item number |
|---|--------|---------------|-------------|
| STREX system surface/suspended | White | 1000-26-29 | 90014181 |
| STREX system custom cut surface/suspended | White | 200-999-26-29 | 90014181CC |
| STREX system surface/suspended | Black | 1000-26-29 | 90014182 |
| STREX system custom cut surface/suspended | Black | 200-999-26-29 | 90014182CC |

Track Profile 2m

| Type | Colour | L·W·H (MM) | Item number |
|--|-----------|-----------------|-------------|
| STREX system suspended indirect light | Black | 2000-26-29 | 900140B5 |
| STREX system custom cut suspended indirect light | Black | 1000-1999-26-29 | 900140B5CC |
| STREX system suspended indirect light | White | 2000-26-29 | 900140W5 |
| STREX system custom cut suspended indirect light | White | 1000-1999-26-29 | 900140W5CC |
| STREX system surface/suspended | White | 2000-26-29 | 90014183 |
| STREX system custom cut surface/suspended | White | 1001-1999-26-29 | 90014183CC |
| STREX system surface/suspended | Black | 2000-26-29 | 90014184 |
| STREX system custom cut surface/suspended | Black | 1001-1999-26-29 | 90014184CC |
| STREX system surface/suspended | Champagne | 2000-26-29 | 90014383 |
| STREX system custom cut surface/suspended | Champagne | 1001-1999-26-29 | 90014383CC |
| STREX system surface/suspended | Bronze | 2000-26-29 | 90014384 |
| STREX system custom cut surface/suspended | Bronze | 1001-1999-26-29 | 90014384CC |

Track Profile 3m

| Type | Colour | L·W·H (MM) | Item number |
|--|-----------|-----------------|-------------|
| STREX system surface/suspended | White | 3000-26-29 | 90014185 |
| STREX system custom cut surface/suspended | White | 2001-2999-26-29 | 90014185CC |
| STREX system surface/suspended | Black | 3000-26-29 | 90014186 |
| STREX system custom cut surface/suspended | Black | 2001-2999-26-29 | 90014186CC |
| STREX system suspended indirect light | Black | 3000-26-29 | 900141B5 |
| STREX system custom cut suspended indirect light | Black | 2001-2999-26-29 | 900141B5CC |
| STREX system suspended indirect light | White | 3000-26-29 | 900141W5 |
| STREX system custom cut suspended indirect light | White | 2001-2999-26-29 | 900141W5CC |
| STREX system surface/suspended | Champagne | 3000-26-29 | 90014385 |
| STREX system custom cut surface/suspended | Champagne | 2001-2999-26-29 | 90014385CC |
| STREX system surface/suspended | Bronze | 3000-26-29 | 90014386 |
| STREX system custom cut surface/suspended | Bronze | 2001-2999-26-29 | 90014386CC |