

RAY

mini 1.0 PAR16

258220M0

GENERAL

Ceiling , Surface

Champagne

IP20

Interior

Output: 360^a, 430^b, 450^c lm

CIE flux code: 94 98 100 100 93

LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 80 to 90

ELECTRICAL

100 - 240 V

LED Inset 4.4^a to 6.5^{b,c} W

Class 1

PHYSICAL

Diameter 70 mm

Height 82 mm

0.14 kg

^a PAR16 LAMP 2700K CRI80

^b PAR16 LAMP 2700K CRI90

^c PAR16 LAMP 3000K CRI90

Project

Type


Notes

Quantity


Date



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Champagne; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; UGR ≤ 19; optional inner reflector available; lamp not included;



LIGHT DISTRIBUTION



RAY

mini 1.0 PAR16

258220M0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	Ø50 · 60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	Ø50 · 60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	Ø50 · 60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	Ø50 · 60	9 0 5 2 2 7 S 4

OPTICAL

Inner Reflector

TYPE	COLOUR	ORDERCODE
RAY mini max. 10W	Black	9 0 0 1 9 9 B 4
RAY mini max. 10W	Gold	9 0 0 1 9 9 G 4
RAY mini max. 10W	Champagne	9 0 0 1 9 9 M 4
RAY mini max. 10W	Bronze	9 0 0 1 9 9 Q 4
RAY mini max. 10W	White	9 0 0 1 9 9 W 4