



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Bronze; wet painted; brushed; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500$ cd/m²; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling
 Surface
 Bronze
 IP20
 Interior
 700 lm
 CIE flux code: 96 100 100 100
 100

LED

3000 K
 CRI ≥ 90
 initial MacAdam ≤ 3 SDCM

OPTICAL


Standard
 beam angle 21°

ELECTRICAL

DALI
 220 - 240 V
 system 8.0 W
 Class 1

PHYSICAL

diameter 114 mm
 height 100 mm
 0.7 kg



[186759Q5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Ø-H (MM)	Item number
RAY max. 10W	Black	67-54	911041B1
RAY max. 10W	Gold	67-54	911041G1
RAY max. 10W	Champagne	67-54	911041M1
RAY max. 10W	White	67-54	911041W1