



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500 \text{ cd/m}^2$; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling _____
 Surface _____
 Black Matt _____
 RAL 9005 ^a _____
 IP20 _____
 Interior _____
 670 lm _____
 CIE flux code: 96 100 100 100 _____
 100 _____

LED

2700 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL

Standard _____
 beam angle 21° _____


ELECTRICAL

phase-cut dim _____
 220 - 240 V _____
 system 8.0 W _____
 Class 1 _____

PHYSICAL

diameter 114 mm _____
 height 100 mm _____
 0.7 kg _____

^a Colour may deviate slightly due to production conditions.



[186758B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



OPTICAL ACCESSORIES

Single Inner Cover

Type	Colour	Ø-H (MM)	Item number
RAY max. 10W	Black	67.54	911041B1
RAY max. 10W	Gold	67.54	911041G1
RAY max. 10W	Champagne	67.54	911041M1
RAY max. 10W	White	67.54	911041W1