



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class 1; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500$  cd/m<sup>2</sup>; optional single inner cover available; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**GENERAL**

Ceiling  
 Surface  
 White Matt  
 RAL 9010 <sup>a</sup>  
 IP20  
 Interior  
 700 lm  
 CIE flux code: 94 99 100 100  
 100

**LED**

3000 K  
 CRI  $\geq 90$   
 initial MacAdam  $\leq 3$  SDCM

**OPTICAL**

Standard  
 beam angle 21°


**ELECTRICAL**

DALI  
 220 - 240 V  
 system 8.0 W  
 Class 1

**PHYSICAL**

diameter 114 mm  
 height 100 mm  
 0.7 kg

<sup>a</sup> Colour may deviate slightly due to production conditions.



[186759W5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**OPTICAL ACCESSORIES**

**Single Inner Cover**

Type	Colour	Ø-H (MM)	Item number
RAY   max. 10W	Black	67.54	911041B1
RAY   max. 10W	Gold	67.54	911041G1
RAY   max. 10W	Champagne	67.54	911041M1
RAY   max. 10W	White	67.54	911041W1