



PROJECT TYPE NOTES QUANTITY DATE





Pendant rod suspension made from aluminium; can be cut and adjusted as desired max. 1950 mm; for ceiling surface mounting; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; CRI (Colour Rendering Index) \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



GENERAL

Ceiling
Surface
Black Matt + Champagne
IP20
Interior
675 lm
CIE flux code: 11 35 66 50 100

LED

 $\frac{2700 \text{ K}}{\text{CRI} \ge 90}$ $\frac{180 \text{ / } 50000\text{h}}{\text{initial MacAdam} \le 3 \text{ SDCM}}$

OPTICAL

Opal

ELECTRICAL

phase-cut dim	
220 - 240 V	
system 7.3 W	
Class 1	

PHYSICAL

diameter 9 mm	
height 1000 mm	
0.43 kg	

FINLIN 2.0

174284CH3



['174284CH3'] The technical data represent rated values for an ambient temperature of 25° C. The data values for the luminous flux are initially subject to a tolerance of +/-10%, those for the electrical connected load are initially subject to a tolerance of +/-10%, and those for the colour temperature are initially subject to a tolerance of +/-10%, and those for the colour temperature are initially subject to a tolerance of +/-10%, and those for the colour temperature are initially subject to a tolerance of +/-10%. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



FINLIN 2.0

174284CH3



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

FINLIN Cover Plate Adapter						
Туре	Colour	Ø·H (MM)	Item number			
for concrete housings	Black	100.3	900194B0			

['174284CH3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply. © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com