

BLIEK petit SURFACE 2.0

164664CH3



PROJECT

TYPE

NOTES

QUANTITY

DATE











Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt + Champagne; powder coated; matt texture + wet painted; smooth semi glossy; inner ring black; with ${\sf COB}$ (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Ceiling
Surface
tilt max 60 °
rotation 355 °
Black Matt + Champagne
IP20
Interior
980 lm
CIE flux code: 99 100 100 100
100

LED

2700 K
CRI ≥ 90
L70 / 55000h
initial MacAdam ≤ 2 SDCM

OPTICAL


Standard	
beam angle 31°	

ELECTRICAL

phase-cut dim	
220 - 240 V	
system 14.2 W	
Class 1	

PHYSICAL

length 230 mm	
width 80 mm	
height 66 mm	
0.65 kg	





BLIEK petit SURFACE 2.0

164664CH3



OPTICAL ACCESSORIES

Honeycomb Louver

Type Colour Ø (MM) Item number BLIEK PETIT | CENO | LECA | PIRRO Black 29 90051131