



PROJECT

---

TYPE

---

NOTES

---

QUANTITY


---

DATE

---



Ceiling surface luminaire with 2 spotlights; made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; inner ring black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2000 K - 3000 K colour warm dimming; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; beam angle 39°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 1; driver included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**GENERAL**

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 tilt max 60 ° \_\_\_\_\_  
 rotation 355 ° \_\_\_\_\_  
 Black Matt \_\_\_\_\_  
 RAL 9005 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 680 lm \_\_\_\_\_  
 CIE flux code: 99 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_  
 2000 K - 3000 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L70 / 55000h \_\_\_\_\_  
 initial MacAdam  $\leq 3$  SDCM \_\_\_\_\_

**OPTICAL**

Standard \_\_\_\_\_  
 beam angle 39° \_\_\_\_\_

**ELECTRICAL**

phase-cut dim \_\_\_\_\_  
 220 - 240 V \_\_\_\_\_  
 system 14.2 W \_\_\_\_\_  
 Class 1 \_\_\_\_\_

**PHYSICAL**

length 230 mm \_\_\_\_\_  
 width 80 mm \_\_\_\_\_  
 height 66 mm \_\_\_\_\_  
 0.65 kg \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions.



**OPTICAL ACCESSORIES**

**Honeycomb Louver**

**Type**

BLIEK PETIT | CENO | LECA | PIRRO

**Colour**

Black

**Ø (MM)**

29

**Item number**

90051131