



PROJECT

TYPE

NOTES

QUANTITY

DATE



GENERAL

Ceiling _____
 Surface _____
 Black Matt _____
 RAL 9005 ^a _____
 IP20 _____
 Interior _____
 1740 lm _____
 CIE flux code: 98 100 100 100 _____
 100 _____

LED

2700 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 initial MacAdam ≤ 3 SDCM _____

OPTICAL


Standard _____
 beam angle 28° _____

ELECTRICAL


phase-cut dim _____
 220 - 240 V _____
 system 26.8 W _____
 Class 1 _____

PHYSICAL

length 322 mm _____
 width 31 mm _____
 height 50 mm _____
 0.38 kg _____



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; beam angle 28°; degree of protection IP20; Class 1; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



^a Colour may deviate slightly due to production conditions.