



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling recessed downlight made from die-cast aluminium; surface White Matt + Black Matt; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; beam angle 28°; degree of protection IP20; Class 3; IC rated; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



GENERAL

Ceiling
 Recessed
 White Matt + Black Matt
 IP20
 IC rated
 Interior
 300 lm
 CIE flux code: 98 100 100 100 100

LED

3000 K
 CRI ≥ 90
 L80 / 50000h
 initial MacAdam ≤ 3 SDCM

OPTICAL

Standard
 beam angle 28°

ELECTRICAL

excl. driver
 12 V
 inset 3.8 W
 Class 3

PHYSICAL

length 66 mm
 width 40 mm
 height 40 mm
 0.07 kg
 wire springs

CUTOUT

length 64 mm
 width 33 mm
 min. ceiling thickness 4 mm
 max. ceiling thickness 25 mm
 recessed depth 60 mm

[129151E5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

129151E5



ELECTRICAL ACCESSORIES

Driver

Type

4.5W | 350 mA | 8-12V | phase-cut dim | IP44

Voltage

8-12V

L·W·H (MM)

49·30·20

Item number

90223101